

H JW_bYgg'; U [Y

H8 A-1 bis H8 A-18



Richard Hess MBV GmbH
Gildestrasse 5

47665 Sonsbeck
Tel. 02838 / 444 o. 1770
Internet: www.hess-mbv.de
E-Mail: info@hess-mbv.de

Modell	Norm	Add`jWUjcb	FcchØ (mm)	Weight (g)	Pressure (kPa)
H8 A-1	ISO 23529 ASTM D 3767	Rubber	4,0	28,0	22,0
H8 A-2	ISO 4593 DIN 53370	Film and Foils	R40,0	10...50	---
H8 A-3	ISO 5084	Textiles	50,5	204,0	1,0
H8 A-4	ASTM D 3767	Rubber with hardness <35 IRHD	16,0	212,0	10,0
H8 A-5	ASTM D 1777 Option 2	Textile Materials, coated fabrics, Webbing Tapes, Ribbons, Braids	9,5	169,0	23,4
H8 A-6	DIN EN ISO 2589	Leather	10,0	393,0	49,1
H8 A-7	ASTM D 1777 Option 3	Films, Glass, cloths, Glass tapes	6,3	546,0	172,0
H8 A-8	ASTM D 5199	Geosynthetics	56,4	509,5	2,0
H8 A-9	DIN EN 534	Paper and Cardboard	16,0	2050,0	100,0
HTG-10	DIN ISO 3034	Cardboard	35,7	2041,0	2,0
H8 A-11	DIN EN ISO 12625-3	Tissue	35,7	204,0	2,0
H8 A-12	DIN EN 1849-2	Flexible sheets for waterproofing	10,0	160,0	20,0
H8 A-13	ASTM D 1777 Option 1	Woven fabrics, knitted fabrics, textured fabrics	28,7	273,0	4,14
H8 A-14	ASTM D 1777 Option 5	Blankets, pile fabrics, napped fabrics	28,7	46,2	0,7
H8 A-15	DIN EN ISO 2286-3 Teil 3	Rubber- or plastics-coated fabrics	10,0	16,0	2,0
H8 A-16	DIN EN ISO 2286-3 Teil 3	Rubber-or plastics-coated fabrics Textilien	10,0	192,2	24,0
H8 A-17	ASTM F 2251	Flexible packaging material	15,875	1033,0	50,3
H8 A-18	ASTM F 2251	Flexible packaging material	6,35	10...150	---

Ihr Ansprechpartner:

Richard Hess MBV GmbH
Gildestrasse 5

47665 Sonsbeck
Tel. 02838 / 444 o. 1770
Internet: www.hess-mbv.de
E-Mail: info@hess-mbv.de